



IK-610L-RV



SPECIFICATION

MODEL	Unit	IK-610L-RV		
<u>Spindle</u>				
Spindle Bore Diameter		NT50		
Diameter of Spindle Nose	mm	Ø128.6		
Spindle Motor	Hp	10 (4P)	12.5 (4P)	15 (4P)
Step of Spindle Speed	stage	6		
Spindle Speed (50Hz)	rpm	88	257	
		132	355	
		173	526	
Spindle Speed (60Hz)	rpm	106	308	
		158	426	
		208	631	
<u>Working Range</u>				
Max Diameter of Cutter	mm	200		
Travel	mm	600(up 300 /down 300)		
Rapid Travel AC Motor		0.4Kw/0.5Hp AC 3 Phase 4 Poles x 1/40		
Rapid Travel Speed	mm/min	177(50Hz) 218(60Hz)		
Reversal Slide		2mm/rev → ← 0.01mm		

※We reserve the right to modify the design and specifications without notice in advance.

STANDARD ACCESSORIES			
Spindle Motor	10HP/4P	12.5HP/4P	15HP/4P
	●	-	-
	-	●	-
	-	-	●
Rapid Travel AC Motor	●		
OPTIONAL ACCESSORIES (APOLEGAMY)			
Pneumatic Blade Locking Device	○		
Bearing Guide Screw	○		
Pneumatic Leveler	○		
IK-A90 Angular Head	○		
IK-D90 Deep Head	○		
IK-U90 Universal Head	○		
IK-U45 Universal Head	○		
Place of Origin	Taiwan		
Weight (Approximate)	kg	630	
Warranty	1 year (non artificial mistake)		

※We reserve the right to modify the design and specifications without notice in advance.

