


IK-610-RV



SPECIFICATION

MODEL	Unit	IK-610-RV	
<u>Spindle</u>			
Spindle Bore Diameter		NT50	
Diameter of Spindle Nose	mm	Φ128.6	
Spindle Motor	Hp	10 / 4P	12.5 / 4P
Step of Spindle Speed	stage	6	
Spindle Speed (50Hz)	rpm	102	345
		153	469
		229	705
Spindle Speed (60Hz)	rpm	123	414
		184	563
		275	846
<u>Working Range</u>			
Max Diameter of Cutter	mm	200	
Travel	mm	398(up 298 /down 100)	
Rapid Travel AC Motor		0.4Kw/0.5Hp AC 3 Phase 4 Poles x 1/40	
Rapid Travel Speed	mm/min	177(50Hz) 218(60Hz)	
Reversal Slide		2mm/rev → ← 0.01mm	

※We reserve the right to modify the design and specifications without notice in advance.

<u>STANDARD ACCESSORIES</u>		
Spindle Motor	10HP / 4P	12.5HP / 4P
	●	-
	-	●
Rapid Travel AC Motor	●	
<u>OPTIONAL ACCESSORIES (APOLEGAMY)</u>		
Pneumatic Blade Locking Device	○	
Bearing Guide Screw	○	
Pneumatic Leveler	○	
IK-A90 Angular Head	○	
IK-D90 Deep Head	○	
IK-U90 Universal Head	○	
IK-U45 Universal Head	○	
Place of Origin	Taiwan	
Weight (Approximate)	kg	508
Warranty	1 year (non artificial mistake)	

※We reserve the right to modify the design and specifications without notice in advance.