



SPECIFICATION

MODEL	Unit	IK-V6000	
<u>SPINDLE</u>			
Tapered Bore Diameter		BT50	
Spindle Speed	rpm	6000	
Speed Change		High / Low	
<u>Deep</u>			
Distance from Spindle to Connector	mm	470	
<u>GEAR RATIO</u>			
High Speed		1:1	
Low Speed		1:4	
Base Speed	rpm	375	
<u>ELECTRIC USE STANDARD</u>			
Spindle Motor	Kw/Hp	11/15	22/30
Spindle Motor Spindle		Ø48	Ø 55
Gear Shift	rpm	1500	
<u>STANDARD ACCESSORIES</u>			
CNC Gear Milling Head - Horizontal Spindle (6000RPM/BT50)	●		
Spindle Motor (Ø 48)	●	-	
Spindle Motor (Ø 55)	-	●	
Lock Knife Block	●		
Shift Cylinder	●		
Oil Pressure Pipe	●		
Place of Origin	Taiwan		
Weight (Approximate)	kg	532	
Warranty	1 year (non artificial mistake)		
Note: This product does not contain a servo motor.			
<u>Recommended specifications</u> §Spindle servo motor (11Kw / 15Hp or 22Kw/30Hp)			
※Please provide a servo motor sizes.			

※**We reserve the right to modify the design and specifications without notice in advance.**